

Reduktion, excentrisk

RFU




Beskrivelse

Excentrisk reduktion med kort byggelængde,

Ød - tilslutningen passer udvendig på Safe faconstykker.

Dimensioner



Ød nom	Ød ₂ nom	cc [mm]	l [mm]	m [kg]
400 *	200	90	80	1,33
400 *	250	65	80	1,44
400 *	315	33	80	1,42
400	355	13	80	0,99
450	250	90	80	1,76
450	315	58	80	1,73
450	355	38	80	1,69
450	400	15	80	1,31
500	250	115	80	2,09
500	315	83	80	2,06
500	355	63	80	1,98
500	400	40	80	2,03
500	450	15	80	1,57
560	315	113	80	2,39
560	355	93	80	2,32
560	400	70	80	2,36
560	450	45	80	1,90
560	500	20	80	1,80
630	315	148	80	2,79
630	355	128	80	2,71
630	400	105	80	2,76
630	450	80	80	2,30
630	500	55	80	2,72
630	560	25	80	2,03
710	400	145	100	3,72
710	450	120	100	2,76
710	500	95	100	3,18
710	560	65	100	2,49
710	630	30	100	2,44
800	400	190	100	3,76
800	450	165	100	3,30
800	500	140	100	3,72

Bestillingskode

Produkt	RFU	630	315
Dimension Ød			
Dimension Ød ₂			



Reduktion, excentrisk

RFU

Ød nom	Ød ₂ nom	cc [mm]	l [mm]	m [kg]
800	560	110	100	3,03
800	630	75	100	3,44
800	710	35	100	2,76
1000	500	240	100	7,34
1000	560	210	100	6,42
1000	630	175	100	6,99
1000	710	135	100	6,24
1000	800	90	100	6,04
1250	630	300	120	11,0
1250	710	260	120	10,3
1250	800	215	120	10,0
1250	1000	115	120	8,86

* Med ombukket kant